

AD-A099 431

GEORGE WASHINGTON UNIV WASHINGTON DC INST FOR MANAGE--ETC F/G 12/1  
NONPARAMETRIC ESTIMATION AND GOODNESS OF FIT TESTING OF HYPOTHE--ETC(U)  
JUL 80 M SHAKED, N D SINGPURWALLA


N00014-77-C-0263

UNCLASSIFIED


SERIAL T-425

NL

1.1  
4 07044



END  
DATE  
FILMED  
6 81  
DTIC



MICROCOPY RESOLUTION TEST CHART  
\* NATIONAL BUREAU OF STANDARDS 1963-A

AD A099431

LEVEL #

(12)  
B5

THE  
GEORGE  
WASHINGTON  
UNIVERSITY

STUDENTS FACULTY STUDY R  
ESEARCH DEVELOPMENT FUT  
URE CAREER CREATIVITY CO  
MMUNITY LEADERSHIP TECH  
NOLOGY FRONTIER DESIGN  
ENGINEERING APPREHENSIVE  
GEORGE WASHINGTON UNIV

FILE COPY

81 5 27 044

SCHOOL OF ENGINEERING  
AND APPLIED SCIENCE



THIS DOCUMENT HAS BEEN APPROVED FOR PUBLIC RELEASE AND SALE; ITS DISTRIBUTION IS UNLIMITED

NONPARAMETRIC ESTIMATION AND GOODNESS OF FIT  
TESTING OF HYPOTHESES FOR DISTRIBUTIONS IN  
ACCELERATED LIFE TESTING

by

(10) Moshe Shaked  
/ Nozer D. Singpurwalla

(14) Serial T-425  
25 July 1980

11 20 Jun 81

(12) 26

The George Washington University  
School of Engineering and Applied Science  
Institute for Management Science and Engineering

\*Grant MCS-79-27150  
National Science Foundation

(15) and

†Contract N00014-77-C-0263, DAFD-77-1-1000  
Office of Naval Research

and

†Grant DAAG 29-80-C-0067  
U.S. Army Research Office

This document has been approved for public  
sale and release; its distribution is unlimited.

406743

NONE

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER T-425	2. GOVT ACCESSION NO. <b>AD-A099431</b>	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) NONPARAMETRIC ESTIMATION AND GOODNESS OF FIT TESTING OF HYPOTHESES FOR DISTRIBUTIONS IN ACCELERATED LIFE TESTING.		5. TYPE OF REPORT & PERIOD COVERED SCIENTIFIC
7. AUTHOR(s) MOSHE SHAKED NOZER D. SINGPURWALLA		6. PERFORMING ORG. REPORT NUMBER T-425
9. PERFORMING ORGANIZATION NAME AND ADDRESS THE GEORGE WASHINGTON UNIVERSITY, SEAS INSTITUTE FOR MANAGEMENT SCIENCE & ENGINEERING WASHINGTON, DC 20052		8. CONTRACT OR GRANT NUMBER(s) NSF Grant MCS-79-27150 N00014-77-C-0263✓ DAAG 29-80-C-0067
11. CONTROLLING OFFICE NAME AND ADDRESS NATIONAL SCIENCE FOUNDATION, WASHINGTON, DC OFFICE OF NAVAL RESEARCH, ARLINGTON, VA U.S. ARMY RESEARCH OFFICE, TRIANGLE PARK, NC		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE 25 July 1980
		13. NUMBER OF PAGES 20
		15. SECURITY CLASS. (of this report)  NONE
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  APPROVED FOR PUBLIC SALE AND RELEASE: DISTRIBUTION IS UNLIMITED.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) ACCELERATED LIFE TESTS TIME TRANSFORMATIONS POWER RULE TESTING HYPOTHESES NONPARAMETRIC METHODS RELIABILITY UNIFORM CONFIDENCE BOUNDS		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) In this paper we present a nonparametric approach to accelerated life testing by deleting the requirement that the common parametric family of life distributions under all the stresses be specified in advance. We do retain the requirement that the time transformation function be specified, and consider a version of the familiar inverse power law. We show how the data from the accelerated life test can be used to obtain a consistent estimate of the failure distribution at use conditions stress, and test (continued)		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

NONE

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

NONE

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. Abstract (continued)

the hypotheses that the underlying failure distributions belong to a specified family of distributions. We also show how to obtain approximate uniform confidence bounds for the failure distribution at use conditions stress. We illustrate our approach by considering some real life data.

NONE

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

THE GEORGE WASHINGTON UNIVERSITY  
School of Engineering and Applied Science  
Institute for Management Science and Engineering

Abstract  
of  
Serial T-425  
25 July 1980

NONPARAMETRIC ESTIMATION AND GOODNESS OF FIT  
TESTING OF HYPOTHESES FOR DISTRIBUTIONS IN  
ACCELERATED LIFE TESTING

by

Moshe Shaked\*  
Nozer D. Singpurwalla†

In this paper we present a nonparametric approach to accelerated life testing by deleting the requirement that the common parametric family of life distributions under all the stresses be specified in advance. We do retain the requirement that the time transformation function be specified, and consider a version of the familiar inverse power law. We show how the data from the accelerated life test can be used to obtain a consistent estimate of the failure distribution at use conditions stress, and test the hypotheses that the underlying failure distributions belong to a specified family of distributions. We also show how to obtain approximate uniform confidence bounds for the failure distribution at use conditions stress. We illustrate our approach by considering some real life data.

---

\*Indiana University, Bloomington, Indiana. Research supported by National Science Foundation Grant MCS-79-27150 with Indiana University.

†The George Washington University, Washington, D.C. Research supported by Office of Naval Research Contract N00014-77-C-0263, and U.S. Army Research Office Grant DAAG 29-80-C-0067 with The George Washington University.

THE GEORGE WASHINGTON UNIVERSITY  
School of Engineering and Applied Science  
Institute for Management Science and Engineering

NONPARAMETRIC ESTIMATION AND GOODNESS OF FIT  
TESTING OF HYPOTHESES FOR DISTRIBUTIONS IN  
ACCELERATED LIFE TESTING

by

Moshe Shaked  
Nozer D. Singpurwalla

1. INTRODUCTION

It is a common practice to subject long-life items to larger than usual stresses so that failure data can be obtained in a short amount of test time. Such tests are called accelerated life tests, and the goal is to infer the mean time to failure, or more generally, the life distribution of the items at the usual stress level using failure data from accelerated tests.

A parametric approach to this problem [3,5,10] involves making two assumptions: first, the life distribution at each stress level is assumed to come from the same parametric family which is *specified*; second, a relationship called the "time transformation function" is assumed among the parameters of the various distributions. As an example of the former, it is typical to assume that the life distributions at the various stress levels are either exponential, Weibull, lognormal, or an extreme value. The time transformation functions which are commonly assumed are the inverse power law, the Arrhenius law, the Eyring law, or generalizations of these. Whereas the above assumptions may be



reasonable in many situations, the possibility does remain that under certain circumstances an analyst may be hesitant or unwilling to entertain any one, or both, of these assumptions.

In this paper, we drop the requirement that the common parametric family of life distributions under all stresses be *specified*, but retain the requirement that the time transformation function be specified. The time transformation function that we consider is a version of the inverse power law. By choosing this form, we do not sacrifice any lack of generality, since the procedures mentioned here can easily be extended to consider the other time transformation functions as well. The inverse power law being commonly used is considered here for purposes of illustration. We indicate how the life distribution and the mean time to failure at use conditions stress can be consistently estimated and how hypotheses about the common parametric family of life distributions can be tested. Thus we are able to test the validity of the distributional assumption traditionally made in accelerated life testing, if the form of the time transformation function can be specified. In another paper [6], both the assumptions mentioned before have been dropped and the problem has been treated completely nonparametrically. However, the statistical precision of the results obtained there is less than that which could be achieved by making one or both of the aforementioned assumptions.

We should remark that the dual problems of estimation and testing for the goodness of fit at use conditions stress have already been considered in two separate papers by Shaked, Zimmer, and Ball [9], and by Sethuraman and Singpurwalla [8]. These papers emphasize technical details pertaining to a formal justification of the methodology, the development of the appropriate formulae, and the performance of the procedures. Thus, a practitioner interested in using the methodologies may find it difficult to extract that information which is pertinent to his goals. Furthermore, the results of the above two papers complement each other and can therefore be combined to constitute a useful package for a nonparametric approach to inference from accelerated life tests.

Our goal in writing this paper is to combine the techniques of [8] and [9] in a manner than is comprehensive and user-oriented so that this nonparametric approach to accelerated life testing is accessible to the reliability analyst. We demonstrate the utility of this approach by applying it to some data from a realistic situation.

## 2. A MODEL FOR ACCELERATED LIFE TESTING

Let  $V_1, V_2, \dots, V_k$  and  $V_0$  denote the accelerated and the use conditions stresses, respectively, and let  $F_1, \dots, F_k$  and  $F_0$  denote the corresponding cumulative distribution functions. We shall assume that  $F_0, \dots, F_k$  belong to a common but unknown family of distributions, and that for some distribution  $F$ , which also belongs to this family,

$$F_i(t) = F(AV_i^\alpha t) \quad , \quad i=0, \dots, k \quad , \quad (2.1)$$

where  $A > 0$  and  $\alpha > 0$  are unknown constants.

This assumption means that a change of stress does not change the shape of the life distribution, but only changes its scale. This model is a generalization of the familiar power law model which is traditionally applied to the scale parameter of the failure distribution [4, 5, 11].

Our goal is to estimate  $F_0$ , the life distribution under use conditions stress, and to perform some goodness of fit tests for hypotheses about the general family of distributions to which  $F$ , and  $F_0, \dots, F_k$ , belong.

## 3. ESTIMATION OF $F_0$

Typically, data from an accelerated life test consists of the set of observations  $T_{i\ell}$ ,  $\ell=1, \dots, n_i$ ,  $i=1, \dots, k$ , where  $T_{i\ell}$  is the time

to failure of the  $l$ th item in a sample of size  $n_i$  that is run under the constant application of stress  $V_i$ ,  $i=1, \dots, k$ . We assume that  $V_1, \dots, V_k$ ,  $k$ , and  $n_1, \dots, n_k$  are all fixed in advance. If data at the nonaccelerated stress level  $V_0$  are also available, then the procedure to be described can still be used, but by augmenting a 0 to the range of indices  $i$  and  $j$  below.

### 3.1 Background

Denote the scale factor between  $F_i$  and  $F_j$  by  $\theta_{ij}$ , where

$$\theta_{ij} = AV_j^\alpha / AV_i^\alpha = (V_j/V_i)^\alpha, \quad i \neq j. \quad (3.1)$$

The first step in the procedure for estimating  $F_0$  is the estimation of  $\alpha$ . A method for estimating  $\alpha$  is suggested by (3.1), since

$$\alpha = \log(\theta_{ij}) / (\log V_j - \log V_i).$$

Let  $\bar{T}_i = n_i^{-1} \sum_{\ell=1}^{n_i} T_{i\ell}$ ,  $i=1, \dots, k$ , be the sample means of the  $T_{i\ell}$ 's,  $\ell=1, \dots, n_i$ . Then, an estimator of  $\theta_{ij}$  is

$$\hat{\theta}_{ij} = \bar{T}_i / \bar{T}_j, \quad i \neq j,$$

from which we can obtain an estimator of  $\alpha$  as

$$\hat{\alpha}_{ij} = \log(\hat{\theta}_{ij}) / (\log V_j - \log V_i), \quad i \neq j.$$

The  $\frac{1}{2}k(k-1)$  estimators of  $\alpha$  can be used to form a weighted average of the  $\hat{\alpha}_{ij}$ 's, which gives us the final estimate of  $\alpha$ , as

$$\hat{\alpha} = \frac{\sum_{i=1}^k \sum_{j=i+1}^k \left( \log(V_j/V_i) \right) \left( \log(\bar{T}_i/\bar{T}_j) \right)}{\sum_{i=1}^k \sum_{j=i+1}^k \left( \log(V_j/V_i) \right)^2}. \quad (3.2)$$

If  $\alpha$  were known, we could, in the light of relationship (2.1), transform (rescale) the times to failure from any stress level to correspond to the times to failure from any other stress level. Thus, observing  $T_{i\ell}$ ,  $\ell=1, \dots, n_i$  under stress  $V_i$  is, under our model, equivalent to observing  $(V_i/V_j)^\alpha T_{i\ell}$ ,  $\ell=1, \dots, n_i$  under stress  $V_j$ . Since  $\alpha$  is not known, we shall use its estimate  $\hat{\alpha}$  to rescale our variables. This is the key notion which enables us to obtain an estimate of  $F_0$ .

### 3.2 Estimation of $F_0$ and the Mean Time to Failure under $V_0$

Using  $\hat{\alpha}$  given by (3.2), we define the  $N = \sum_{i=1}^k n_i$  rescaled variables

$$\tilde{T}_{i\ell} = \left( \frac{V_i}{V_0} \right)^{\hat{\alpha}} T_{i\ell}, \quad \ell=1, \dots, n_i, \quad i=1, \dots, k, \quad (3.3)$$

and estimate  $F_0$  by the empirical distribution function of the  $\tilde{T}_{i\ell}$ 's. Thus,  $\hat{F}_0$ , an estimator of the failure distribution at use conditions stress  $V_0$ , is given by

$$\hat{F}_0(t) = \frac{1}{N} \{\text{number of observations among the } \tilde{T}_{i\ell} \text{'s } \leq t\},$$

for  $0 \leq t < \infty$ . (3.4)

An estimator of the mean time to failure at use conditions stress, say  $\hat{\mu}$ , is given by

$$\hat{\mu} = \frac{1}{N} \sum_{i=1}^k \sum_{\ell=1}^{n_i} \tilde{T}_{i\ell} = \sum_{i=1}^k \frac{n_i}{N} \left( \frac{V_i}{V_0} \right)^{\hat{\alpha}} \bar{T}_i. \quad (3.5)$$

The estimators  $\hat{F}_0$  and  $\hat{\mu}$  are  $s$ -consistent [9]. A method for obtaining the approximate  $s$ -uniform confidence limits for  $F_0$  using  $\hat{F}_0$  is discussed in Section 5.

4. GOODNESS OF FIT TESTING OF HYPOTHESES FOR  $F_0$ 

Having estimated  $F_0$  by  $\hat{F}_0$  given by (3.4), our next goal is to see if  $F_0$  is a member of a specified family of distribution functions. This type of information may be of interest in its own right, or it can be used to obtain s-uniform confidence bounds for  $F_0$ . Testing to see if  $F_0$  is a member of a specified family is equivalent to testing whether  $F_1, \dots, F_k$  are also members of the same family. For reasons given in [8], it is convenient for us to consider the random variables  $X_{i\ell} = \log T_{i\ell}$ ,  $\ell=1, \dots, n_i$ ,  $i=1, \dots, k$ , and test for the underlying distribution of the  $X_{i\ell}$ 's, say  $H_i$ ,  $i=1, \dots, k$ . For example, if we wish to test the hypothesis that the  $F_i$ 's are members of the family of Weibull distributions, then this is equivalent to testing whether the  $H_i$ 's are members of the family of extreme value distributions [3]. Similarly, if we wish to test the hypothesis that the  $F_i$ 's are members of the lognormal family of distributions, then this is equivalent to testing whether the  $H_i$ 's are normal [3].

There are two limitations to our testing procedure. The first one is that we can only work with complete (uncensored) samples, and the second one is that the  $H_i$ 's can only be tested for being members of the s-location-scale family of distributions. The commonly used members of the s-location-scale family are the normal, the exponential, and the extreme-value distributions. Since  $H_i$  is an exponential distribution whenever  $F_i$  is a Pareto distribution, and since a Pareto distribution is rarely used to describe life lengths, the desire for testing whether  $H_i$  is an exponential is not very common.

The procedure for testing depends upon the particular family of distributions that is being considered; this will be made clear in the

following section. Furthermore, the procedure is valid when each of the  $n_i$ 's is large.

#### 4.1 Testing Whether $F_0$ is a Weibull

Suppose that we wish to test the hypothesis that the common underlying family of distributions is a Weibull distribution. This is equivalent to testing whether the  $H_i$ 's are extreme value distributions

$$H_i(x) = 1 - \exp \left\{ -\exp \left( \frac{x - \alpha_i}{\beta_i} \right) \right\}, \quad i=1, \dots, k,$$

where  $\alpha_i$  and  $\beta_i$  are the s-location and the s-scale parameters, respectively. The test procedure entails the following steps.

- (1) Using  $X_{i\ell}$ ,  $\ell=1, \dots, n_i$ , we first obtain the s-maximum likelihood estimates of  $\alpha_i$  and  $\beta_i$ , say  $\hat{\alpha}_i$  and  $\hat{\beta}_i$ , respectively, using the above specified  $H_i$ . Methods for obtaining these estimates are given in [3]; they can also be obtained using the computer program discussed in Section 4.3.
- (2) For  $0 < t \leq 1$ , we compute

$$W_i(t) = \frac{1}{n_i} \sum_{\ell=1}^{n_i} I \left( H_i \left( \frac{X_{i\ell} - \hat{\alpha}_i}{\hat{\beta}_i} \right) \leq t \right),$$

where

$$H_i \left( \frac{X_{i\ell} - \hat{\alpha}_i}{\hat{\beta}_i} \right) = 1 - \exp \left\{ -\exp \left( \frac{X_{i\ell} - \hat{\alpha}_i}{\hat{\beta}_i} \right) \right\},$$

and  $I\{E\}$  denotes the indicator of the event  $E$ . Verify that  $W_i(t)$  is merely the empirical distribution function of the  $H_i \left( (X_{i\ell} - \hat{\alpha}_i) / \hat{\beta}_i \right)$ ,  $\ell=1, \dots, n_i$ .

- (3) We then compute, for  $0 \leq t \leq 1$ ,

$$\tilde{V}_i(t) = \sqrt{n_i} (W_i(t) - t),$$

and repeat the Steps (1), (2), and (3) for all values of  $i$ ,  $i=1, \dots, k$ .

- (4) Our test statistic  $D$  is the s-Kolmogorov-Smirnov statistic obtained by pooling the  $\tilde{V}_i(t)$ 's in a manner shown below. Let

$$A = n_i / \sum_{i=1}^k n_i, \text{ and let}$$

$$Z(t) = \sum_{i=1}^k A_i \tilde{V}_i(t), \quad 0 \leq t \leq 1.$$

Then  $D = \max(D^+, -D^-)$ , where

$$D^+ = \max_{0 \leq t \leq 1} \left( \sum_{i=1}^k A_i^2 \right)^{-1/2} Z(t), \text{ and}$$

$$D^- = \min_{0 \leq t \leq 1} \left( \sum_{i=1}^k A_i^2 \right)^{-1/2} Z(t).$$

- (5) We will accept the hypothesis that the common underlying family of distributions is a Weibull (i.e., the  $H_i$ 's are extreme value distributions) at a desired level of significance, say  $\alpha$ , if the value  $D$  is less than the critical values given below. These values have been abstracted from [2].

Level of Significance, $\alpha$	.10	.05	.025	.01
Critical Values of $D$ , $D^*$	.800	.870	.940	1.000

#### 4.2 Testing Whether $F_0$ is Lognormal

Testing to see if the common underlying family of distributions is a lognormal is equivalent to testing whether the  $H_i$ 's are normal distributions,

$$H_i(x) = \int_{-\infty}^x \frac{1}{\sqrt{2\pi}\beta_i} \exp\left(-\frac{1}{2}\left(\frac{u-\alpha_i}{\beta_i}\right)^2\right) du,$$

$i=1, \dots, k$ , where the  $\alpha_i$  and  $\beta_i$  are the s-location (mean) and s-scale (standard deviation) parameters, respectively. The test procedure entails the following steps.

- (1) Using  $X_{i\ell}$ ,  $\ell=1, \dots, n_i$ , we obtain

$$\hat{\alpha}_i = \sum_{\ell=1}^{n_i} X_{i\ell} / n_i \quad \text{and} \quad \hat{\beta}_i^2 = \sum_{\ell=1}^{n_i} (X_{i\ell} - \hat{\alpha}_i)^2 / (n_i - 1),$$

the s-maximum likelihood estimators of  $\alpha_i$  and  $\beta_i$ , respectively.

- (2) We repeat steps (2), (3), and (4) of Section 4.1, except that now

$$H_i\left(\frac{X_{i\ell} - \hat{\alpha}_i}{\hat{\beta}_i}\right) = \int_{-\infty}^{X_{i\ell}} \frac{1}{\sqrt{2\pi}\hat{\beta}_i} \exp\left(-\frac{1}{2}\left(\frac{u - \hat{\alpha}_i}{\hat{\beta}_i}\right)^2\right) du,$$

$\ell=1, 2, \dots, n_i$ , and to test for the significance of  $D$ , we use the following critical values abstracted from [7].

Level of Significance, $\alpha$	.10	.05	.025	.01
Critical Values of $D$ , $D^*$	.752	.835	.910	.991



### 4.3 Some Comments on the Test Procedure

The power of the above tests against various alternatives is discussed in [8]. The main point here is that it is difficult to distinguish between the Weibull and the lognormal alternatives, so that the final choice of the family of distributions to which  $F_0$  belongs must be based on criteria other than a formal goodness of fit test. For example, if the hazard rate is known to be increasing in time, then the distribution cannot be lognormal and the Weibull assumption should be chosen.

To aid in the computation of  $D$ , and also the  $s$ -maximum likelihood estimates  $\hat{\alpha}_i$  and  $\hat{\beta}_i$  for the various hypotheses that we wish to entertain, we have written a computer program, described in [1]. This program can be made available to the interested reader.

### 5. UNIFORM CONFIDENCE BOUNDS FOR $F_0$

The approximate  $s$ -uniform  $(1-\alpha)\%$  confidence bounds for  $F_0$  can be obtained once a test of hypothesis results in the acceptance of the hypothesis. The approximate confidence bounds will be based on  $\hat{F}_0$  given by (3.4) and the critical values  $D^*$  given in Section 4.1 and 4.2. (The confidence bounds are approximate because of the finiteness of the sample sizes, and because they are based on  $\hat{F}_0$  and not on a complicated transformation of  $\{Z(t), t \geq 0\}$  of Section 4.) These bounds can also be used to obtain an approximate  $(1-\alpha)\%$   $s$ -confidence bound on  $\hat{\mu}$ , the median of the time to failure distribution under  $V_0$ .

Suppose that the procedure of Section 4.1 results in our accepting the hypothesis that the  $H_i$  are extreme value distributions. This means that  $F_0$  is a Weibull distribution, so that the approximate uniform  $(1-\alpha)\%$  confidence limits for  $F_0$  are given by

$$\hat{F}_0(t) \pm D^*/\sqrt{N},$$

where  $D^*$  is the critical value of  $D$  corresponding to  $\alpha$ , and  $N = \sum_{i=1}^k n_i$ . For example, if we choose  $\alpha = .05$ , then the approximate 95% uniform upper and lower confidence limits for  $F_0$  are

$$g(t) = \hat{F}_0(t) + .870/\sqrt{N},$$

and

$$h(t) = \hat{F}_0(t) - .870/\sqrt{N},$$

respectively. In computing the above, we should make sure to confine both  $g(t)$  and  $h(t)$  to be between 0 and 1.

In a similar manner, if the procedure of Section 4.2 results in our acceptance of the hypothesis that  $F_0$  is a lognormal distribution, then the 95% uniform confidence bounds for  $F_0(t)$  will be  $\hat{F}_0(t) \pm .835/\sqrt{N}$ .

The uniform confidence bounds  $g(t)$  and  $h(t)$  can be used to obtain an approximate s-confidence bound for  $\tilde{\mu}$  by taking their inverses. Thus, the approximate s-confidence bounds for  $\tilde{\mu}$  are  $g^{-1}(.5)$  and  $h^{-1}(.5)$ , where  $g^{-1}(.5) < h^{-1}(.5)$ .

## 6. EXAMPLE

We apply the methodology of this paper to some accelerated life test data given in [4] and [5]. These data represent the times to breakdown of an insulating fluid subjected to seven elevated voltage levels. Since the methodology of Section 4 is valid for large sample sizes, and since three of the stress levels of [5] contain too few failures, we delete them from our consideration, and consider an abstracted version of the data. These data are given in Table 1, and have also been considered in [6]. The use conditions stress corresponds to  $V_0 = 20$  kilovolts.

TABLE 1  
TIMES TO BREAKDOWN OF AN INSULATING FLUID  
(IN MINUTES) UNDER VARIOUS VALUES OF THE  
STRESS

36 kV	34 kV	32 kV	30 kV
.35	.19	.27	7.74
.59	.78	.40	17.05
.96	.96	.69	20.46
.99	1.31	.79	21.02
1.69	2.78	2.75	22.66
1.97	3.16	3.91	43.40
2.07	4.15	9.88	47.30
2.58	4.67	13.95	139.07
2.71	4.85	15.93	144.12
2.90	6.50	27.80	175.88
3.67	7.35	53.24	194.90
3.99	8.01	82.85	
5.35	8.27	89.29	$N_4 = 11$
13.77	12.06	100.58	
25.50	31.75	215.10	
$N_1 = 15$	32.52	$N_3 = 15$	
	33.91		
	36.71		
	72.89		
	$N_2 = 19$		

### 6.1 Estimation of $F_0$

Using the failure times given in Table 1, we obtain via (3.2) an estimate of  $\alpha$ ,  $\hat{\alpha} = 16.9844$ ; note that this estimate is different from the estimate obtained in [9], since there, all the data of [5] were used. We then rescale the data in Table 1 using (3.3), with  $\hat{\alpha} = 16.9844$  and  $V_0 = 20$ , and use these to compute the empirical distribution function  $\hat{F}_0$ , given by (3.4). This is our estimate of  $F_0$ , and

is given in Figure 1. The median of these rescaled variables is easily verified as being 45572 minutes, and an estimate of  $\mu$ , obtained from (3.5), is  $\hat{\mu} = 105998$  minutes. Other s-percentiles of  $F_0$  can also be estimated using  $\hat{F}_0$ .

## 6.2 Testing Hypotheses

A plot of the logarithms of the 60 rescaled observations mentioned in Section 6.1 on normal probability paper, Figure 2, suggests that the logarithms of the failure times could be well described by a normal distribution.

The plot of Figure 2 suggests that we test for normality by taking  $H_i$ ,  $i=1,2,3,4$ , to be normal distributions. Our estimates  $(\hat{\alpha}_i, \hat{\beta}_i)$  turn out to be (.902, 1.109), (1.786, 1.525), (2.228, 2.198), and (3.821, 1.111);  $D$  is computed as .4023. From the table of critical values given in Section 4.2 we see that for  $\alpha = .05$ ,  $D^* = .835$ , and since  $D < D^*$ , we have no reason to reject the null hypothesis that the failure times of Table 1 could be described by a lognormal distribution.

The approximate 95% uniform confidence limits for  $F_0$  are obtained as  $\hat{F}_0(t) \pm .835/\sqrt{60}$ , and these are shown by the dotted lines of Figure 1. The 95% confidence interval for  $\tilde{\mu}$  discussed in Section 5 is obtained by reading the ordinates of the horizontal line at .5 in Figure 1; these turn out to be 32,320 and 64,000 minutes.

Since a Weibull distribution for times to failure has been assumed in [5], it is appropriate that we test for this distribution as well. We thus take  $H_i$ ,  $i=1,\dots,4$  to be an extreme value distribution and compute  $(\hat{\alpha}_i, \hat{\beta}_i)$  as (1.473, 1.154), (2.531, 1.353), (3.310, 1.898), and (4.373, .987); we obtain  $D$  as .88. From the table of




Figure 1. Empirical distribution function  $\hat{F}_0$  of the 60 rescaled observations of Table 1, the approximate 95% uniform confidence limits for  $\hat{F}_0$ , and a confidence interval for  $\tilde{\mu}$ .




Figure 2. A plot of the logarithms of the 60 rescaled observations on normal probability paper.

critical values given in Section 4.3 we see that for  $\alpha = .05$ ,  $D^* = .87$ . Thus  $D$  is significant at the 95% level of significance, but barely so.

Thus it appears that for this abstracted set of data, either the lognormal or the Weibull distribution would provide an adequate description, with the lognormal having a slight edge over the Weibull. In choosing between these two, one should remember that even though the formal goodness of fit tests favor the lognormal, the Weibull with its monotone failure rate may be a more appropriate distribution for describing the times to failure. The failure rate of a lognormal distribution first increases and then decreases, and this may not be realistic for the situation considered here.

## REFERENCES

- [1] ARSHAM, H. and N. D. SINGPURWALLA (1980). A computer program for testing hypotheses for distributions in accelerated life tests. Technical Paper, Institute for Management Science and Engineering, The George Washington University.
- [2] CHANDRA, M.; N. D. SINGPURWALLA; and M. STEPHENS (1980). Kolmogorov statistics for tests of fit for the extreme value and Weibull distributions with estimated parameters. To appear.
- [3] MANN, N. R.; R. E. SCHAFER; and N. D. SINGPURWALLA (1974). *Methods for Statistical Analysis of Reliability and Life Data*. Wiley, New York.
- [4] NELSON, W. B. (1972). Graphical analysis of accelerated life test data with inverse power law model. *IEEE Trans. Reliability*, R-21, 195.
- [5] NELSON, W. B. (1975). Analysis of accelerated life test data--least squares methods for the inverse power law model. *IEEE Trans. Reliability*, R-24, 103-107.
- [6] PROSCHAN, F. and N. D. SINGPURWALLA (1980). A new approach to inference from accelerated life tests. *IEEE Trans. Reliability*, R-29, 98-102.
- [7] SERFLING, R. J. and C. L. WOOD (1976). On null hypothesis limiting distributions of Kolmogorov-Smirnov type statistics with estimated location and scale parameters. Technical Report, Florida State University, Tallahassee.



- [8] SETHURAMAN, J. and N. D. SINGPURWALLA (1980). Testing of hypothesis for distributions in accelerated life tests. Technical Paper, Institute for Management Science and Engineering, The George Washington University.
- [9] SHAKED, M.; W. J. ZIMMER; and C. A. BALL (1979). A nonparametric approach to accelerated life testing. *J. Amer. Statist. Assoc.*, 74, 694-699.
- [10] SHAKED, M. (1978). Accelerated life testing for a class of linear hazard rate type distributions. *Technometrics*, 20, 457-466.
- [11] SINGPURWALLA, N. D. (1971). A problem in accelerated life testing. *J. Amer. Statist. Assoc.*, 66, 841-845.

OFFICE OF NAVAL RESEARCH  
STATISTICS AND PROBABILITY PROGRAM

BASIC DISTRIBUTION LIST  
FOR  
UNCLASSIFIED TECHNICAL REPORTS

JANUARY 1981

	Copies		Copies
Statistics and Probability Program (Code 436) Office of Naval Research Arlington, VA 22217	3	Office of Naval Research Scientific Liaison Group Attn: Scientific Director American Embassy - Tokyo APO San Francisco 96503	1
Defense Technical Information Center Cameron Station Alexandria, VA 22314	12	Applied Mathematics Laboratory David Taylor Naval Ship Research and Development Center Attn: Mr. G. H. Gleissner Bethesda, Maryland 20084	1
Office of Naval Research New York Area Office 715 Broadway - 5th Floor New York, New York 10003	1	Commandant of the Marine Corps (Code AX) Attn: Dr. A. L. Slafkosky Scientific Advisor Washington, DC 20380	1
Commanding Officer Office of Naval Research Eastern/ Central Regional Office Attn: Director for Science 666 Summer Street Boston, MA 02210	1	Director National Security Agency Attn: Mr. Stahly and Dr. Maar (R51) Fort Meade, MD 20755	2
Commanding Officer Office of Naval Research Western Regional Office Attn: Dr. Richard Lau 1030 East Green Street Pasadena, CA 91101	1	Navy Library National Space Technology Laboratory Attn: Navy Librarian Bay St. Louis, MS 39522	1
Commanding Officer Office of Naval Research Branch Office Attn: Director for Science 536 South Clark Street Chicago, Illinois 60605	1	U. S. Army Research Office P.O. Box 12211 Attn: Dr. J. Chandra Research Triangle Park, NC 27706	1

	Copies		Copies
OASD (ISL), Pentagon Attn: Mr. Charles S. Smith Washington, DC 20301	1	ATAA-SL, Library U. S. Army TRADOC Systems Analysis Activity Department of the Army White Sands Missile Range, NM 88002	1
ARI Field Unit-USAREUR Attn: Library c/o ODCSPER HQ USAEREUR & 7th Army APO New York 09403	1	Technical Library Naval Ordnance Station Indian Head, MD 20640	1
Naval Underwater Systems Center Attn: Dr. Derrill J. Bordelon Code 21 Newport, Rhode Island 02840	1	Defense Logistics Studies Information Exchange Army Logistics Management Center Attn: Mr. J. Dowling Fort Lee, VA 23801	1
Library, Code 1424 Naval Postgraduate School Monterey, CA 93940	1	Reliability Analysis Center (RAC) RADC/RBRAC Attn: I.L. Krulac Data Coordinator Government Programs Griffiss AFB, New York 13441	1
Technical Information Division Naval Research Laboratory Washington, DC 20375	1	Mr. F. R. Del Priori Code 224 Operational Test and Evaluation Force (OPTEVFOR) Norfolk, VA 23511	1
Dr. Barbara Bailar Associate Director, Statistical Standards Bureau of Census Washington, DC 20233	1	Mr. Jim Gates Code 9211 Fleet Material Support Office U. S. Navy Supply Center Mechanicsburg, PA 17055	1
Director AMSAA Attn: DRXSY-MP, H. Cohen Aberdeen Proving Ground, MD 21005	1	Mr. Ted Tupper Code M-311C Military Sealift Command Department of the Navy Washington, DC 20390	1
Dr. Gerhard Heiche Naval Air Systems Command (NAIR 03) Jefferson Plaza No. 1 Arlington, VA 20360	1	Mr. Barnard H. Bissinger Mathematical Sciences Capitol Campus Pennsylvania State University Middletown, PA 17057	1
B. E. Clark RR #2, Box 647-B Graham, NC 27253	1	Morton L. Buckberg Naval Sea Systems Command (NSEA 3133) National Center No. 2 Arlington, VA 20360	1
Leon Slavin Naval Sea Systems Command (NSEA 05H) Crystal Mall #4, Rm. 129 Washington, DC 20036	1		

# THE GEORGE WASHINGTON UNIVERSITY

BENEATH THIS PLAQUE  
IS BURIED

A VAULT FOR THE FUTURE  
IN THE YEAR 2036

THE STORY OF ENGINEERING IN THIS YEAR OF THE PLACING OF THE VAULT AND  
ENGINEERING HOPES FOR THE TOMORROWS AS WRITTEN IN THE RECORDS OF THE  
FOLLOWING GOVERNMENTAL AND PROFESSIONAL ENGINEERING ORGANIZATIONS AND  
THOSE OF THIS GEORGE WASHINGTON UNIVERSITY.

BOARD OF COMMISSIONERS DISTRICT OF COLUMBIA  
UNITED STATES ATOMIC ENERGY COMMISSION  
DEPARTMENT OF THE ARMY UNITED STATES OF AMERICA  
DEPARTMENT OF THE NAVY UNITED STATES OF AMERICA  
DEPARTMENT OF THE AIR FORCE UNITED STATES OF AMERICA  
NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS  
NATIONAL BUREAU OF STANDARDS U.S. DEPARTMENT OF COMMERCE  
AMERICAN SOCIETY OF CIVIL ENGINEERS  
AMERICAN INSTITUTE OF ELECTRICAL ENGINEERS  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
THE SOCIETY OF AMERICAN MILITARY ENGINEERS  
AMERICAN INSTITUTE OF MINING & METALLURGICAL ENGINEERS  
DISTRICT OF COLUMBIA SOCIETY OF PROFESSIONAL ENGINEERS, INC.  
THE INSTITUTE OF RADIO ENGINEERS, INC.  
THE CHEMICAL ENGINEERS CLUB OF WASHINGTON  
WASHINGTON SOCIETY OF ENGINEERS  
FAULKNER KINGSBURY & STENHOUSE ARCHITECTS  
CHARLES H. TOMPKINS COMPANY BUILDERS  
SOCIETY OF WOMEN ENGINEERS  
NATIONAL ACADEMY OF SCIENCES NATIONAL RESEARCH COUNCIL

THE PURPOSE OF THIS VAULT IS INSPIRED BY AND IS DEDICATED TO

**CHARLES HOOK TOMPKINS, DOCTOR OF ENGINEERING**

BECAUSE OF HIS ENGINEERING CONTRIBUTIONS TO THIS UNIVERSITY, TO HIS  
COMMUNITY, TO HIS NATION, AND TO OTHER NATIONS.

BY THE GEORGE WASHINGTON UNIVERSITY

ROBERT W. FLEMING

CHAIRMAN OF THE BOARD OF TRUSTEES

CLOYD H. MARVIN

PRESIDENT

THE GEORGE WASHINGTON UNIVERSITY  
1955

To cope with the expanding technology, our society must be assured of a continuing supply of rigorously trained and educated engineers. The School of Engineering and Applied Science is completely committed to this objective.

DATE  
FILME